

HUBEI TIANRUI ELECTRONIC CO.,LTD.

TRDP-30*20



Products Features


TRDP series current transformers are easy to install, and can be operated with electricity without disconnecting the wires once, without affecting the normal installation and use of customers.

Application


TRDP series current transformers are mainly used for the measurement and protection of electrical equipment in 0.66kV AC power system, and can also be used together with relay protection, measurement and metering devices, which are widely used in the transformation of urban and rural power networks.

Mechanical dimension

Dimension (mm)



Electrical schematic diagram



HUBEI TIANRUI ELECTRONIC CO.,LTD.

Technical data

					•
Transformation Ratio	100/5A	200/5A	250/5A	300/5A	400/5A
Rated Capacity(0.5 class)	1	1	1	1.5VA	2.5VA
Rated Capacity(1.0 class)	1	1.5VA	1.5VA	3.75VA	5VA
Rated Capacity(1.5 class)	1.5VA	2.5VA	3.75VA	5VA	10VA
Frequency	50Hz/60Hz				
Inner Diameter	22.5*32.5mm				
Tolerance	± 1.5mm				
Power Frequency Withstand Voltage	3kV AC/1min				
Ambient Operating Temperature	-25°C~70°C				
Ambient Storage Temperature	-40°C~75°C				

Contact information

HUBEI TIANRUI ELECTRONIC CO.,LTD.

Add: No.8 Chuangye Road, Econommic Development Zone, Tianmen 431700, Hubei, China

Website: www.hbtrec.com
Email: export@hbtianrui.com